

AURO^P

Mono Bifacial Half Cell Module

530-555W MLTK-36

Key Product Features



High power output

Using 182mm size Mono wafer
Module power output up to 555W



Higher mechanical load capacity

Adopt high-strength aluminum alloy frame
Mechanical performance up to 5400 Pa
positive load and 2400 Pa negative load



Bifacial design

Double-sided power generation
Power gain up to 5%~25%



High compatibility

Excellent system compatibility
Adapt to mainstream inverter and tracker



Low temperature coefficient

Peak power temperature coefficient
Excellent power generation performance in
high temperature environment



Wide applicability

Harsh environments
Wider range of application



Excellent low-light performance

Better low-light power generation performance
in low radiation environment such as haze and
cloudy days



Low LCOE (Levelized Cost of Energy)

The cost of BOS reduced by 1.48%
LCOE reduced by 1.27%

Comprehensive product certification

- IEC61215-1(ed.1)
- IEC61215-1-1(ed.1)
- IEC61215-2(ed.1)
- IEC61730-1(ed.2)
- IEC61730-2(ed.1)
- UL 61730-1 1st Edition
- UL 61730-2 1st Edition




Industry-leading Quality Assurance

12 year
Product warranty

25 year
linear power warranty

-0.55%
Annual degradation



● Please refer to the warranty letter for details



Solar Power



Add: No.3009 BYD Road, Pingshan District, Shenzhen

+86-755-89888888

bydpv@byd.com

Electrical Data(STC*)

Module Type: MLTK-36	530	535	540	545	550	555
Rate Maximum Power(Pmax)(W)	530	535	540	545	550	555
Open Circuit Voltage(Voc) (V)	49.12	49.42	49.72	50.02	50.32	50.62
Short Circuit Current(Isc) (A)	13.45	13.49	13.53	13.57	13.61	13.65
Maximum Power Voltage(Vmp)(V)	41.61	41.83	42.05	42.27	42.49	42.71
Maximum Power Current (Imp) (A)	12.74	12.79	12.84	12.89	12.94	12.99
Module Efficiency (%)	20.52	20.71	20.90	21.10	21.29	21.48

*Standard Test Conditions (STC) : irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C

Electrical Data(NMOT*)

Module Type: MLTK-36	530	535	540	545	550	555
Rate Maximum Power(Pmax)(W)	395.2	398.8	402.4	406.1	409.8	413.4
Open Circuit Voltage(Voc) (V)	45.9	46.2	46.5	46.8	47.0	47.3
Short Circuit Current(Isc) (A)	10.86	10.89	10.92	10.96	10.99	11.02
Maximum Power Voltage(Vmp)(V)	38.4	38.7	38.9	39.1	39.4	39.6
Maximum Power Current (Imp) (A)	10.28	10.31	10.34	10.37	10.40	10.44

*Nominal Module Operating Temperature (NMOT):irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

Operational Parameter

Operating Temperature	-40°C~+85°C				
NMOT (Nominal Module Operating Temperature)	45°C±2°C				
Maximum System Voltage(V)	1500V DC				
Maximum Fuse Current Rating(A)	30A				
Fire Safety	Class C				
Power Tolerance	0~+5W				
Bifacial Factor	70±5%				
PG. 530W	5%	10%	15%	20%	25%
Rate Maximum Power(Pmax)(W)	557	583	610	636	663
Open Circuit Voltage(Voc) (V)	49.12	49.12	49.12	49.12	49.12
Short Circuit Current (Isc) (A)	14.12	14.80	15.47	16.14	16.81
Maximum Power Voltage(Vmp)(V)	41.61	41.61	41.61	41.61	41.61
Maximum Power Current(Imp) (A)	13.377	14.014	14.651	15.288	15.925


Mechanical Properties

Cell Type	P - type Mono-crystalline
Number of Cells	144
Dimension of Module	2278*1134*35mm
Weight	27kg ± 5%
Front Glass	3.2mm tempered glass with AR Coating
Frame	Anodized aluminum alloy
Junction Box	IP68(3 Diodes)
Cable Length	+320mm , -260mm(4.0mm ²) ; or Customized Length
Packing Information	620(31*20)pics per 40'HQ

Temperature Coefficient

Peak Power Temperature Coefficient	-0.332%/°C
Open-Circuit Voltage Temperature Coefficient	-0.252%/°C
Short-Circuit Current Temperature Coefficient	0.046%/°C

Drawing



I-V curve

